



COVER FASTENED WITH SHEET METAL SCREWS



- A - COVER HEIGHT BASED ON THICKNESS OF ANCHOR BASE.
- B - COVER WIDTH BASED ON SIZE OF ANCHOR BASE.
- C - SHAFT CUTOUT BASED ON SHAFT SIZE AND SHAPE.

**FINISH: BASE COVER TO BE STANDARD POLYESTER POWDER COAT FINISH.**

 <p style="font-size: small;">P.O. Box 340 Eastpointe, MI 48021 P: (586) 771-4610   F: (586) 771-5527 www.lytepoles.com a DWM company</p>	DRAWN: M. HARVALA	2/16/2015	SOME GEOGRAPHICAL AREAS HAVE SPECIAL WIND CONDITIONS THAT CAN CREATE WIND INDUCED VIBRATIONS CAUSING A FATIGUE PROBLEM. NO METHOD HAS YET BEEN FOUND FOR PREDICTING DESTRUCTIVE LIGHTING POLE VIBRATION. THESE CONDITIONS ARE UNIQUE AND CANNOT BE GUARANTEED AGAINST, AND ARE THE RESPONSIBILITY OF A LOCAL SITE ENGINEER.		
	CHECKED				TITLE:
	REVISION:	DATE:			CATALOG:
	APPROVED:				DWG NO: CSBC
	QUOTE:				SIZE C
	S.O.#	SCALE: NONE			SHEET 1 OF 1